

## Saffire EVO LZ-M

# **Cloud-Connected Smart Mortise Lock**



#### **Applications**

- Ideal for new construction projects or retrofits
- Get real-time notifications including events and access anomalies
- Manage access rights to allow or revoke access for residents and visitors in real-time, from anywhere
- Easily send digital keys or PIN codes to residents and visitors from a mobile device
- Residents can use their mobile device, RFID credentials, or PIN to access their residence or common areas
- Provide convenient one-time or recurring access PINs to service and maintenance personnel
- Control when and where residents and visitors can go throughout the building
- Lost access media can be quickly deleted to keep the building secure

#### Overview

Saffire EVO LZ-M is a cloud-connected RFID lock that combines high-performance with aesthetics, seamlessly integrating with building technology providers and amenities for multihousing properties.

The Saffire EVO LZ-M provides an easy-to-use, secure, and flexible solution with the benefits of real-time connectivity. It includes the convenience of using either mobile devices, RFID credentials or secure PINs for access to resident units, common areas and perimeter doors.

#### Security with IoT connectivity

The Saffire EVO LZ-M is equipped with Wi-Fi onboard, ensuring connectivity to the dormakaba Lyazon cloud and seamless integration to our Lyazon partner platforms for real-time events and user notifications. Online connectivity of the Saffire EVO LZ-M also provides continuous updates for built-in device security.


#### Designed for our aggregator partners

The Saffire EVO LZ product lineup is specifically designed to be integrated with our dormakaba Lyazon partner platforms to ensure a premium user experience for multifamily residents. The dormakaba Saffire EVO LZ cloud-connected smart locks allow

easy access management of residences, amenities, common areas and perimeters, all through a single integrated platform.

#### Security features

- Online connectivity ensures continuous firmware updates for increased device security
- BHMA A156.13 Grade 1 pending
- UL 10C 3-hour fire rating
- Non-volatile memory maintains lock programming and audit records
- Staff monitoring with RFID keycard audits
- Tamperproof design
- No need to visit the lock to update access



#### **Mechanical Features**

**Description** Online connectivity ensures continuous updates for increased device security. Supports dormakaba RFID,

Bluetooth®, and keypad credentials

**Handing** Left or right factory handed mortise, field reversible handing (lever and mortise)

Levers Troy, Essen, and Von levers (field reversible). Custom lever options available, consult with your sales representative

Finishes Trim finishes: satin chrome C (626), oil-rubbed bronze Z (613)\*\*, bright chrome R (625), satin nickel N (619) and

black K (622). Polycarbonate: black (B), graphite gray (R), white (W)

**Door Thickness** From 1 3/8" to 2 1/2" (35 mm to 66 mm)

Standard Backset ASM: 2 3/4" (70 mm)

Locking Options ANSI Grade 1 mortise lock case with 1 1/4" or 1" lock front mortise with optional automatic deadbolt

Batteries 3 AA . Low battery indicator for preventative maintenance is both local visual and event notification populated in

system. Passive warning and notification

Concealed Key Override Optional: Lori KIK core (keyed-alike, master key)

Electronic Battery

Backup

Electronic lock power supply (ELPS) battery back-up. ELPS part number 118-515990

Wi-Fi Online Control Wi-Fi 802.11 b/g/n WPA2, WPA AES 128 and TLS 1.2>/-70dB signal strength at the lock

#### Mobile Access

Bluetooth® Enabled Bluetooth® Low Energy 2.4 GHz version 4.2, iOS or Android mobile device support, AES 128 and DTLS security,

supported through partner mobile app

<sup>\*\*</sup> Oil-rubbed bronze is a PVD finish

#### **Lock Operation**

**No Touring** New credentials applied to lock through Wi-Fi

application

**Date/time Stamp** Real time: date and hours/minutes; automatically adjusts for daylight savings time

Audit Trail Audit trail managed through Wi-Fi. 5,000 events

Passage Mode Set by authorized key

Lockout Mode Set by authorized key

Toggle Mode Use of credential is needed to "lock" the door after exiting unit, this stops accidental resident lockouts and

delivers full audit trail to ownership/management

Credential Formats dormakaba ComID high security credentials 13.56MHz MIFARE DESFire EV3 ISO card or fob / Mobile access

credentials (Bluetooth®) / 6 digit PIN codes

Feedback LED Light indicators

 Diagnostics
 Lock diagnostics through partner application

 Privacy Override
 Default emergency key only (user selectable)

### Certifications &

Testing

Certification ANSI/BHMA A156.25 pending, ANSI/BHMA A156.13 Grade 1 pending, Florida Building Code HVHZ / Non-HVHZ

Accessibility Standard Complies with 2010 ADA Standards for Accessible Design. Must be installed according to ADA and local requirements

**Fire Rating** Meets UL 10C and ULC S-104, on fire door rated up to and including 3 hours

Electronics Compliant with RED Directive 2014/53/EU for electromagnetic compatibility and FCC part 15 and RSS-247

Industry Canada requirements

Environmental
Operating Conditions

-31°F to 158°F (-35°C to 70°C), 0% to 90% non-condensing humidity at 86°F (30°C) Meets IP54

#### Warranty

Standard Warranty Two years

Any questions? We would be happy to advise you.

Contact us on: 1800 849 8324